

- ▶ 90° × 90°
- ▶ 15"
- ▶ JBL 2408-2
- ▶ 15 mm DuraFlex™
- ▶ M10 35 mm
- ▶
- ▶
- ▶ JBL COMMERCIAL



CV3015/99 JBL  
15"

CV3015/99 15"  
JBL 2408-2

CV3015/99

90° × 90°

CV3015/99

CV3015/99 M10 35 mm  
CV3015/99

NL4

Neutrik Speakon® CV3015/99 DuraFlex™

CV3015/99

CV3015/99

-10 dB	<sup>1</sup>	45 Hz – 20 kHz					
±3dB	<sup>1</sup>	75 Hz – 20 kHz					
		90°×90°					
IEC	<sup>2</sup>	<sup>3</sup>	400 W / 800 W / 1600 W	/	/		
		1m	<sup>2</sup>	125 dB	131 dB		
		2.83V@1m	<sup>1</sup>	99 dB			
				8 Ω			
				1 × 15"	3"		
				1 × 2408-2	1.5"		
				20°	15mm		
				13 M10	3@ 35mm	3@ OmniMount	2@ 3@ ×
				DuraFlex™			
				1.5 mm			
				NL4 Neutrik Speakon®			
		H × W × D		680 mm × 414.4 mm × 445 mm			
				26.8 in × 16.3 in × 17.5 in			
				23.15 kg 51.0 lbs			

1 4π  
2  
3 IEC 6 dB 2

▶ CV3 09 15

110

100

0

mm inc

