

# VRX915S 15" Bass Reflex Subwoofer

**Professional Series**

**Key Features:**

- ▶ In egral rigging hard are for smple connec ion of VRX915S line-arras and op onal arra frame.
- ▶ 15 inch, 2265G-1 Differen ial Dri e oofer for e ended lo -freq enc o p
- ▶ Ligh and compac for ersa ili and eas handleabili .
- ▶ 20 mm hreaded pole socke for solid, sec re sa elli e speaker mon ing

**Applications:**

- ▶ Li e performance s s ems
- ▶ Mobile and ed DJ s s ems
- ▶ So nd s s em ren al and o r
- ▶ Permanen ins alla ions.

The VRX915S is a compac , high po er s s pendable s b oofer s s em con aining a 2265G-1 neod m m magne , pa en ed Differen ial Dri e , 15" oofer in a fron -loaded, en ed enclos re. The VRX915S as designed speci call for use in arras i h he VRX928LA Line Arra speaker and VRX-SMAF Arra Frame. In addi ion i ma also be used in arras consis ing en irel of VRX915S s b oofers.

The s s em offers comple e inp connec ion e ibili for compa ibili i h a arie of cabling schemes. A recessed, e rnal s i ch allo s selec ion of ei her con acs +1/-1 or +2/-2 o be ro ed o he oofer.

Eq all a home in gro nd s acked applica ions, he VRX915S is eq ipped i h a op-mo n ed, hreaded, 20 mm socke ha can recei e he op onal SS4-BK pole. This ad s able heigh pole can be used o mo n speakers eq ipped i h s andard 36 mm pole sockes. The hreaded socke minimizes b zzing and raling and ass res ha he pole ill be sec re and s raigh .

The enclos re is cons rced of op q ali birch pl ood, coa ed in JBL s r gged D raFle m nish and is hea il braced o ma imize lo -freq enc performance. The a rac i e CNC-machined, 16-ga ge s eel grille is ernall lined i h ac s icall ransparen foam o pro ide addi onal dri er pro ec ion and gi e a er professonal appearance. The rear of he enclos re is ed i h T-n s i hich ma be used o a ach he op onal WK-4 cas er ki .



Sho n i h VRX928LA and op onal VRX-SMAF Arra Frame




**Specifications:**

S s em T pe:	15" bass re e s b oofer
Freq enc Range (-10 dB):	35 Hz - 250 Hz
Freq enc Respon e (-3 dB):	40 Hz - 250 Hz
Recommended Hi-Pass Fil er:	High-pass: B er or h 24 dB/oc , 45 Hz Lo -pass: Link i z-Rile 48 dB/oc , 80 - 120 Hz
Po er Ra ing <sup>1</sup> : (Con in o s / Program / Peak)	800 W / 1600 W / 3200 W
Ma im m Peak SPL <sup>2</sup> :	126 dB SPL
Sensi i (1 @ 1m):	91 dB SPL
LF Dri er:	1 JBL 2265G-1, 380 mm (15 in) Differen ial Dri e oofer
Nominal Impedance:	4 Ohms
Ac i e T nings:	T nings a ailable a jblpro.com
Enclos re:	15 mm - 18 mm, m l i pl birch pl ood
S s pension / Mo n ing:	Top mo n ed M20 hreaded socke for op onal pole SS4-BK. In egral ed ing hard are for use i h arra frame VRX-SMAF. 8 M10 ngs. Op onal M10 e ebol ki .
Transpor :	In egral ed s eel handle i h backing o p
Finish:	Black D raFle m nish
Grille:	Po der coa ed, black, 16 ga ge perfora ed s eel i h ac s icall ransparen black foam backing.
Inp Connec ons:	Ne rik Speakon NL-4 ( 2)
Inp connec ion modes:	S i cable, +1/-1 or +2/-2
Dimens ions (H W D):	496 mm 420 mm 597 mm (19.5 in 16.5 in 23.5 in)
Ne Weigh :	26 kg (57 lb)

<sup>1</sup>IEC 1 ered noise i h 6 dB cres fac or, 2 ho s.  
<sup>2</sup>Calcula ed, based on po er ra ing and sensi i .

JBL con in all engages in research rela ed o prodc impro emen . Some ma rials, prodc ion me hods and design re nemen s are in roced in o e is ing prodc s i ho no ice as a ro ine e press ion of ha philosoph . For his reason, an o ren JBL prodc ma differ in some respec from is p blished descp ion, b ill all a s eq al or e ceed he original descp ion speci ca ions nless o her ks s a ed.

# ▶ VRX915S 15" Bass Reflex Subwoofer



LOW  
FREQ

8500 Bannock  
Northridge, Calif

**H** A H a m a l e a l C m a

SS  
CRF  
03/07